



STEAM SHOWER CHEAT SHEET

TCNA Details

- SR 613- Commercial and Residential with continuous use
- SR 614- Residential only with intermittent use

Tile

Most porcelain and ceramic tiles are suitable for steam shower installations, but you'll want to check with the manufacturer to ensure it is recommended for steam showers. Natural stone, as a general rule, is not recommended due to its porous nature.

Membranes

Membranes require a waterproof membrane with a perm rating of 0.5 or less.

- **Laticrete:** Hydro Ban- Requires use of vapor barrier behind the substrate
- **TEC:** Hydra Flex- Requires use of vapor barrier behind the substrate
- **Schluter:** Kerdi DS (commercial or residential), Kerdi/Kerdi Board (residential only)

Thinset

Thinsets should meet or exceed ANSI 118.15

- **Laticrete:** 254 Platinum, 257 Titanium, Tri Lite, 4XLT
- **TEC:** Super Flex, Ultimate 6 Plus, Ultimate
- **Schluter:** All Set

Cement Grout

Cement grout should meet or exceed ANSI 118.6

- **Laticrete:** Perma Color, Perma Color Select
- **TEC:** Power Grout

Sealant/Caulk

Sealant/Caulk should be 100% Silicone

- **Laticrete:** Latacil
- **TEC:** AccuColor 100